

Belvedere™ Flags

Product & Technical Data



At Kilsaran Lifestyle we produce our full range of paving and Landscape products in our state-of-the-art computerised manufacturing facility at Dunboyne, Co. Meath.

We are committed to ensuring that our entire product range meets and exceeds all National and European Standard Requirements. Kilsaran operate Quality Control procedures throughout the process and all of our paving block range is subjected to full testing in accordance with IS EN 1339:2003 using the latest technology in our purpose-built Paving Products Laboratories.

| Product & Depth | Dimensions (LxW) | Pieces per m ² |
|---|---|---------------------------|
| Belvedere 60m Flag Set (only available in a 4 size mixed bale) | 7 pieces per m2 (2 No 200x200) (2 No 400x400) (2 No 600x400) (1 No 400x200) | 7 |

| | |
|--------------------|---|
| Colours Available: | Curled Silver Granite, Curled Stone, Curragh Gold, Yellow. Other colours to special order |
|--------------------|---|

| Technical & Performance Data | |
|---------------------------------|---|
| Manufacturer: | Kilsaran Lifestyle, Piercetown, Dunboyne, Co. Meath, Ireland. |
| Manufacturing Standard : | IS EN 1339:2003 |
| Manufacturing Method: | Hydraulically pressed semi-dry concrete, bush-hammered. |
| Constituents: | Aggregates, sand, admixtures, cement, colour pigments |
| Packaging: | Baled, strapped and plastic wrapped. |
| Strength: | Class 1, Typical Bending strength of $\geq 2,8\text{MPa}$ |

Structural Design

Paving Flags are suited more to pedestrianised areas and areas which receive only very light traffic, eg private driveway with no turning movements. Structural design of pavements incorporating concrete flag paving should be carried out in accordance with BS 7533 Part 8 and it may also be useful to read this in conjunction with the Interpave guidance manual 'Structural Design of Concrete Flag Pavements' available from www.interpave.org. Also refer to our Concrete Paving Flag Technical Guidance Document which is available in hard copy or by download from our website at www.kilsaranlifestyle.ie.

Blending

When selecting paving flags from packs during laying, select alternative pieces from at least three different packs where possible to minimise colour variation on the finished pavement. Further guidance on installation and specifications of concrete flag pavements is available from Interpave on their website www.interpave.org or by contacting our Technical Department at technical@kilsaran.ie or by calling +353 (0)1 802 6300

Disclaimer:

All figures given are approximate only. The above data serves as a guideline only. Kilsaran LifeStyle does not accept responsibility for the design and construction of concrete block pavements by third parties. As concrete block paving is made from naturally occurring aggregates some slight and normal colour variation may occur. Efflorescence may occur as a naturally occurring phenomenon when temporary white stains may appear on the block surface. Kilsaran LifeStyle cannot accept responsibility for these natural occurrences. Through the use of the most modern photographic techniques available we endeavor to ensure that the colour illustrations of our products in this data sheet are as accurate as possible. We do recommend that any final decision is based upon viewing a sample of the product. These samples can be provided by our Sales team, Specifications team, paving centres stocking our product (see www.kilsaranlifestyle.ie), your paving/landscape contractor, or at our manufacturing facility in Dunboyne, County Meath.